

JP03101752
IMAGE FORMING DEVICE
CANON INC

Inventor(s): ; NAGOSHI SHIGEYASU

Application No. 01238383, Filed 19890916, Published 19910426

Abstract: PURPOSE: To control a change in an S-D gap and fluctuation in the circumferential speed of a photosensitive drum caused by vibration, etc., by pressing-contact a photosensitive drum part and a developing sleeve part to a main body by an elastic member and firmly fixing them.

CONSTITUTION: The photosensitive drum part A and the developing sleeve part B are housed in a housing 8, and the photosensitive drum part A and the developing sleeve part B are pressed so as to be brought into contact with the main body and firmly fixed by the elastic member 16 and 17. Then, the firm fixation of the photosensitive drum part A and the developing sleeve part B in a process cartridge K to the main body is prevented from becoming unstable because of the vibration. Thus, the change in the S-D gap and the fluctuation in the circumferential speed of the photosensitive drum A can be controlled and the occurrence of a failure such as irregularities in a printing pitch, etc., can be eliminated, so that a good image can be always obtained in a stable state.

COPYRIGHT: (C)1991,JPO&Japio

Int'l Class: G03G01500;

MicroPatent Reference Number: 000155404

COPYRIGHT: (C)JPO

BEST AVAILABLE COPY